



INDUSTRIES 3R

Danville Office
55, route 116 Ouest
Danville (Québec) Canada
J0A 1A0

Phone: 819-839-2793
Fax: 819-839-2797
Toll-free: 800-567-2728
E-mail: info@industries3r.com

GRAPHITE LUBRICANT

3R3020



Description

Excellent aerosol dry-film lubricant that prevents sticking and seizing. It air dries quickly, can be applied to metal, wood and plastics. The 3R3020 provides a smooth film. Also, it is not greasy, is non-flammable, it conducts electricity without being magnetic. The propellant is « ozone friendly » since the environmentally harmful CFCs have been eliminated. This material is available in 12 oz aerosol cans.

Applications

Gates
Transfer wheels
Coating dies for storage
Monorails
Printed circuits
Hose reels
Belt & chain guides
Release coating for core boxes
Turnstiles
Mold release
Spark plug threads
Winch drums
Truck roll-up doors
Garage doors
Overhead crane rails

Specifications

Physical properties

Temperature	-34°C to 426°C (-30°F to 800°F)
Physical Properties	Air dries quickly-requires no baking Can be applied to all metal, wood and plastic surfaces Greaseless, oil-free - will not pick up dirt or grit Electrically conductive, non-magnetic Good lubrication, metal release, anti-weld

N.B. The information presented may differ from practice. We recommend conducting tests according to the conditions of use. We accept no responsibility for results obtained by the application of this information or the safety and suitability of our products. The data is subject to certain variations without notice.