



INDUSTRIES 3R

Danville Office
55, route 116 Ouest
Danville (Québec) Canada
J0A 1A0

Phone: 819-839-2793
Fax: 819-839-2797
Toll-free: 800-567-2728
E-mail: info@industries3r.com

TEFLON

3R810



Description

The PTFE (polytetrafluoroethylene) is a polymer, one of the most versatile plastics known to man. The 3R810 sheet can handle virtually all chemicals in the 0-14 pH range with the exception of molten alkali metals and elemental fluorine. The 3R810 is recommended for applications in the industrial and process industries. It is more economical than the virgin PTFE.

Applications

The 3R810 is recommended for applications in the industrial and process industries. It is more economical than the virgin PTFE.

Specifications

Technical Data

Temperature	-200°C to 260°C (-325°F to 500°F)
Color	White
Thickness	1/64", 1/32", 1/16", 3/32", 1/8", 3/16", 1/4"
Sizes	48" X 48", 60" X 60" or 48" X 60" (rolls)
Tensile strength at 73°F (ASTM D638-61T)	1500-2400psi
Elongation (ASTM D638-61T)	75-20%
Water absorption (ASTM D570-59aT)	0.001%
Dielectric constant (1000cps)(ASTM D150-59T)	2.26
Dielectric strength in air (ASTM D257-61)	450 volts/mil.

N.B. The information presented may differ from practice. We recommend conducting tests according to the conditions of use. We accept no responsibility for results obtained by the application of this information or the safety and suitability of our products. The data is subject to certain variations without notice.