



INDUSTRIES 3R

Danville Office
55, route 116 Ouest
Danville (Québec) Canada
J0A 1A0

Phone: 819-839-2793
Fax: 819-839-2797
Toll-free: 800-567-2728
E-mail: info@industries3r.com

FIBERGLASS

TXP405



Description

The TXP405 is a satin weaved fiberglass fabric coated with a silver rubberized silicone. It resists abrasion, flexing, tearing and puncturing. It protects from water, oil and chemical products and generates little smoke.

Applications

This fabric is used for removable blankets, expansion joints, welding curtains and flexible connectors.

Specifications

Technical Data

Temperature	50°C to 260°C (-55°F to 500°F)
Color	Grey
Weight	32oz/yd ²
Thickness	0.035"
Flame Resistance	Flame out (sec) 1 sec. Max. Afterglow (sec) 1 sec. Max. Char length (in) 1/16" max.
Tensile strength	Wrap 500 lbs/in min. average, Fill 400 lbs/in min. average
Tear Strength	Wrap 75 lbs min. average, Fill 40 lbs min. average
Mullen Burst	400 psi min. average

N.B. The information presented may differ from practice. We recommend conducting tests according to the conditions of use. We accept no responsibility for results obtained by the application of this information or the safety and suitability of our products. The data is subject to certain variations without notice.