



INDUSTRIES 3R

Danville Office

55, route 116 Ouest
Danville (Québec) Canada
J0A 1A0

Phone: 819-839-2793

Fax: 819-839-2797

Toll-free: 800-567-2728

E-mail: info@industries3r.com

FIBERGLASS

TXP600



Description

The Texpro 600 fabric is produced with high quality texturized fibreglass yarns. Used either to insulate or protect, this fabric is flexible and adaptable to many applications. It does not burn nor emit harmful smoke or vapors when exposed to high temperatures, will not mold and resists to most acids and alkali.

Applications

The TXP 600, thicker than the other fiberglass fabrics, is suitable for rigorous applications. It is used as heat shields, fire blankets, welding curtains, protection apparels, to make high temperature removable blankets, stress relieving pads, expansion joints and gaskets. Other typical applications include wrapping tools, pipes, cables to protect against other internal or external high temperatures.

Specifications

Technical Data

Weight	60oz/yd ²
Thickness	0.090"
Width	40", 60"
Temperature	continue: 535°C (1000°F), Brief excursion: 645°C (1200°F)
Length	50 yd/roll

N.B. The information presented may differ from practice. We recommend conducting tests according to the conditions of use. We accept no responsibility for results obtained by the application of this information or the safety and suitability of our products. The data is subject to certain variations without notice.