



INDUSTRIES 3R

Danville Office
55, route 116 Ouest
Danville (Québec) Canada
J0A 1A0

Phone: 819-839-2793
Fax: 819-839-2797
Toll-free: 800-567-2728
E-mail: info@industries3r.com

FIBERGLASS

TXP660S



Description

This tubing is made of 100% fiberglass and is covered with high temperature red silicone. Flexible, it adjusts itself to imperfect surfaces and around sharp corners.

Applications

Used to cover pipes and tubes to make a static seal, the TXP660S offers an excellent protection from molten metal splashes up to 3000°F.

Specifications

Technical Data

Temperature	Fiberglass: 535°C (1000°F), Silicone: 260°C (500°F)
Diameter	3/8", 1/4", 1/2", 5/8", 3/4", 7/8", 1", 1-1/8", 1-1/4", 1-1/2", 1-3/4", 2", 2-1/4", 2-1/2", 2-3/4", 3", 3-1/4", 3-1/2", 3-3/4", 4", 4-1/2"
Length	50, 100 feet/roll
Nominal wall thickness	0.142" (3.61mm)

N.B. The information presented may differ from practice. We recommend conducting tests according to the conditions of use. We accept no responsibility for results obtained by the application of this information or the safety and suitability of our products. The data is subject to certain variations without notice.